

7.2.5. Data Types

7.2.5.1. ModeOptionStruct Type

The table below lists the changes relative to the Mode Base cluster for the fields of the ModeOptionStruct type. A blank field indicates no change.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Label						M
1	Mode						M
2	ModeTags		1 to 8				M

7.2.6. Attributes

The table below lists the changes relative to the Mode Base cluster for the attributes. A blank field indicates no change.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	SupportedModes						
0x0001	CurrentMode						
0x0002	StartupMode						X
0x0003	OnMode						X

7.2.6.1. SupportedModes Attribute

At least one entry in the SupportedModes attribute SHALL include the Idle mode tag in the ModeTags field.

At least one entry in the SupportedModes attribute (different from the one above) SHALL include the Cleaning mode tag in the ModeTags field.

The Mapping, Cleaning, and Idle mode tags are mutually exclusive and SHALL NOT be used together in a mode's ModeTags.

7.2.7. Derived Cluster Namespace

This namespace includes definitions for data associated exclusively with the derived cluster.

7.2.7.1. ChangeToModeResponse Command Namespace Definitions

The following table defines the derived cluster specific StatusCode values.