

process. [SAE J2847/3_202311] version and IEC61841 define Pilot signal as a modulated DC voltage on a single wire.

Power Line Communication (PLC) is supported by some EVSEs (e.g. for support of ISO 15118 in Europe and SAE J2931/4 in NA) and may enable features such as Vehicle to Grid (V2G) or Vehicle to Home (V2H) that allows for bi-directional charging/discharging of electric vehicles.

More modern EVSE devices may optionally support ISO 15118-20 in Europe and SAE J2836/3 for NA to support bi-directional charging (Vehicle to Grid - V2G) and Plug and Charge capabilities.

This cluster definition assumes AC charging only. DC charging options may be added in future revisions of this cluster.

This cluster supports a safety mechanism that may lockout remote operation until the initial latching conditions have been met. Some of the fault conditions defined in SAE J1772, such as Ground-Fault Circuit Interrupter (GFCI) or Charging Circuit Interrupting Device (CCID), may require clearing by an operator by, for example, pressing a button on the equipment or breaker panel.

This EVSE cluster is written around support of a single EVSE. Having multiple EVSEs at home or a business is managed by backend system and outside scope of this cluster.

Note that in many deployments the EVSE may be outside the home and may suffer from intermittent network connections (e.g. a weak Wi-Fi signal). It also allows for a charging profile to be pre-configured, in case there is a temporary communications loss during a charging session.

9.3.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Updates after 0.7 Ballot review
3	Added Q quality for SessionDuration, SessionEnergyCharged and SessionEnergyDischarged. Updates to V2X and associated areas. Make PREF mandatory.
4	Sync with SDK revision number

9.3.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	EEVSE

9.3.3. Cluster ID