

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	StartDate	epoch-s	min StartDate	X			M
1	DayPatternIDs	list[uint32]	1 to 7				M

9.12.5.9.1. StartDate Field

This field SHALL indicate the timestamp in UTC when the calendar period becomes active.

A null value SHALL indicate the calendar period becomes active immediately. See [CalendarPeriods](#) attribute.

9.12.5.9.2. DayPatternIDs Field

This field SHALL indicate a list of [DayPatternIDs](#) for the [DayPatternStructs](#) in use during this calendar period.

If any of the [DayPatternStructs](#) referenced by this list has no bits set in [DaysOfWeek](#), then none of the [DayPatternStructs](#) referenced by this list SHALL have any bits set, and the list SHALL be treated as a rotating set of days.

If at least one of the [DayPatternStructs](#) referenced by this list has a bit set in [DaysOfWeek](#), then:

1. All of the [DayPatternStructs](#) referenced by this list SHALL have at least one bit set in [DaysOfWeek](#)
2. No two [DayPatternStructs](#) referenced by this list SHALL have the same bit set in [DaysOfWeek](#).
3. Every bit defined in [DayPatternDayOfWeekBitmap](#) referenced by this list SHALL be set in [DaysOfWeek](#) on one of the [DayPatternStructs](#).

Meeting these constraints ensures that every day of the week during this week has specified day entries, and no day of the week has more than one set of day entries.

9.12.5.10. DayEntryStruct Type

This struct represents a day entry at a particular time of day, along with an optional duration and randomization parameters.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	DayEntryID	uint32	all				M
1	StartTime	uint16	max 1499				M
2	Duration	uint16	max (1500 - StartTime)				O