

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
3	Random-izationOffset	int16	all				[RNDM]
4	Random-ization-Type	DayEntryRandomizationTypeEnum	all		None		[RNDM]

9.12.5.10.1. DayEntryID Field

This field SHALL indicate an identifier for the day entry which is unique on the server to a set of values:

1. If this identifier is included in the [DayEntryIDs](#) associated with a [DayPatternStruct](#), then the identifier SHALL be unique to the combination of:
 - a. the [StartTime](#)
 - b. the [Duration](#), if indicated
 - c. the [DaysOfWeek](#) field in the containing [DayPatternStruct](#)
2. Otherwise, if this identifier is included in the [DayEntryIDs](#) associated with a [DayStruct](#), then the identifier SHALL be unique to the combination of:
 - a. the [StartTime](#)
 - b. the [Duration](#), if indicated
 - c. the [Date](#) field in the containing [DayStruct](#)

Once an identifier has been used for a given combination above, it SHALL never be used for any other combination of these values.

9.12.5.10.2. StartTime Field

This field SHALL indicate the start time of the [DayEntryStruct](#), expressed as the number of minutes that have elapsed since midnight on the associated days.

For example, 6am will be represented by 360 minutes since midnight and 11:30pm will be represented by 1410 minutes since midnight.

This will differ on days with a day entry in or out of daylight saving time. For example, if the implementation of daylight saving time in a region means that the hour between 2am and 3am will be skipped on the day entry into daylight saving time, then 2am cannot be represented, and 3am will be represented by 120 minutes.

Similarly, if the implementation of daylight saving time in a region means that the hour between 2am and 3am will be repeated on the date of day entry out of daylight saving time, then the first 2am will be represented by 120 minutes, while the second 2am will be represented by 180 minutes,