

9.12.5.12. DayPatternStruct Type

This represents a series of day entries over the course of a day for a given set of days of the week.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	DayPatternID	uint32	all				M
1	DaysOfWeek	DayPatternDay-OfWeek-Bitmap	all				M
2	DayEntryIDs	list[uint32]	1 to 96				M

9.12.5.12.1. DayPatternID Field

This field SHALL indicate an identifier for the day pattern. It SHALL be a unique identifier for the combination of values of the [DaysOfWeek](#) and [DayEntryIDs](#) fields.

Once an identifier has been used for this combination, it SHALL NOT be used to represent any other combination of these values.

9.12.5.12.2. DaysOfWeek Field

This field SHALL indicate which days of the week the associated set of [DayEntryStructs](#) applies to. If no bits are set, then this SHALL be a rotating day. See [DayPatternIDs](#).

9.12.5.12.3. DayEntryIDs Field

This field SHALL indicate a list of [DayEntryIDs](#) for the [DayEntryStructs](#) to apply during the days specified by [DaysOfWeek](#), ordered by [StartTime](#).

This list SHALL NOT contain two [DayEntryIDs](#) for the [DayEntryStructs](#) with the same value of the [StartTime](#) field.

9.12.5.12.3.1. Day Coverage

The [DayEntryStruct](#) referenced by the first [DayEntryID](#) in this list SHALL have its [StartTime](#) field set to zero.

Every [DayEntryStruct](#) referenced by this list SHALL have its [Duration](#) field omitted.

Meeting these constraints ensures that there are no periods during the day which are not covered by a [DayEntryStruct](#).

9.12.5.13. PeakPeriodStruct Type