

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0026	Local-SnapshotRecordingEnabled	bool	all	N		RW M	SNP & STOR
0x0027	Status-LightEnabled	bool	all	N	1	RW M	O
0x0028	Status-Light-Brightness	ThreeLevelAutoEnum	all	N		RW M	O

11.2.7.1. MaxConcurrentEncoders Attribute

This attribute SHALL indicate the maximum number of concurrent encoders supported by the camera.

11.2.7.2. MaxEncodedPixelRate Attribute

This attribute SHALL indicate the maximum data rate in encoded pixels per second that the camera can produce given the hardware encoder resources it has. This value is manufacturer specified.

If the camera supports Snapshots and requires hardware encoder resources to produce those Snapshots, then this attribute SHALL be present, and a manufacturer specific value SHALL be present in each [SnapshotCapabilities MaxFrameRate](#) entry that requires hardware resources to produce.

11.2.7.3. VideoSensorParams Attribute

This attribute SHALL indicate the set of video sensor [parameters](#) for the camera. These include the video sensor dimensions, its frame rate and HDR capabilities.

11.2.7.4. NightVisionUsesInfrared Attribute

This attribute SHALL indicate if the night vision mode is infrared based or not. A value of TRUE indicates infrared mode with a cut filter being used. A value of FALSE indicates color is used. When infrared is active and the resulting content is in black and white, the [BlackAndWhiteActive](#) field inside any produced [AVMetadataStruct](#) SHALL be TRUE.

11.2.7.5. MinViewportResolution Attribute

This attribute SHALL indicate the minimum resolution (width and height) in pixels that the camera allows for its viewport.

The choice of the minimum viewport width and height is, typically, directed towards maintaining the best image quality (reduced distortion) for a given size of the video sensor, for different camera functions, e.g., digital zoom. Furthermore, the minimum viewport size and the video sensor size