

11.2.8.1.5. BitRate Field

This field SHALL indicate the bitrate of the specified audio codec in bits per second. The default bitrate MAY vary based on the type of device and codec.

11.2.8.1.6. BitDepth Field

This field SHALL indicate the number of bits of information (8, 16, 24 or 32 bits) used to represent each sample of the audio signal.

11.2.8.1.7. Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the requested StreamUsage is not found in the [StreamUsagePriorities](#) attribute:
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- If an unsupported AudioCodec, ChannelCount, SampleRate, BitRate, or BitDepth is requested:
 - Fail the command with the status code DYNAMIC_CONSTRAINT_ERROR, and end processing with no other side effects.
- If there is an existing stream in [AllocatedAudioStreams](#) that matches this request:
 - Return the existing AudioStreamID in [AudioStreamAllocateResponse](#), and end processing with no other side effects.
- If there are not enough resources to allocate a new audio stream:
 - Fail the command with the status code RESOURCE_EXHAUSTED, and end processing with no other side effects.
- Allocate a new AudioStreamID
- Create and store a new [AudioStreamStruct](#) for the allocated stream mapped against the new AudioStreamID.
- Append the new [AudioStreamStruct](#) to the [AllocatedAudioStreams](#).
- Return the newly allocated AudioStreamID in [AudioStreamAllocateResponse](#).

11.2.8.2. AudioStreamAllocateResponse Command

This command SHALL be sent by the camera in response to the AudioStreamAllocate command, carrying the newly allocated or re-used audio stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	AudioStreamID	AudioStreamIDType	all			M

11.2.8.2.1. AudioStreamID Field

The AudioStreamID field SHALL be a [AudioStreamIDType](#) representing the unique audio stream