

identifier.

11.2.8.3. AudioStreamDeallocate Command

This command SHALL deallocate an audio stream on the camera, corresponding to the given audio stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	AudioStreamID	AudioStreamIDType	all			M

11.2.8.3.1. AudioStreamID Field

The AudioStreamID field SHALL be a [AudioStreamIDType](#) representing the unique audio stream identifier for the stream that needs to be deallocated.

11.2.8.3.2. Effect on Receipt

The process below SHALL be followed by the camera when receiving this command:

- If the AudioStreamID does not match an entry in [AllocatedAudioStreams](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the reference count for the stream with AudioStreamID is greater than 0:
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- If the StreamUsage for the stream with AudioStreamID is [Internal](#):
 - Fail the command with the status code DYNAMIC_CONSTRAINT_ERROR, and end processing with no other side effects.
- Deallocate the audio stream with AudioStreamID.
- Remove the entry for AudioStreamID from [AllocatedAudioStreams](#).
- Respond with the status code SUCCESS.

11.2.8.4. VideoStreamAllocate Command

This command SHALL allocate a video stream on the camera and return an allocated video stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0x00	StreamUsage	StreamUsageEnum	Recording, Analysis, LiveView			M