

with no other side effects.

- If [DigitalPTZ](#) is supported in [Camera AV Settings User Level Management](#):
 - Remove the entry for VideoStreamID from [DPTZStreams](#).
- Deallocate the video stream with VideoStreamID.
- Remove the entry for VideoStreamID from [AllocatedVideoStreams](#).
- Respond with the status code SUCCESS.

11.2.8.8. SnapshotStreamAllocate Command

This command SHALL allocate a snapshot stream on the device and return an allocated snapshot stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0x00	ImageCodec	ImageCodecEnum	all			M
0x01	MaxFrameRate	uint16	min 1			M
0x02	MinResolution	VideoResolutionStruct				M
0x03	MaxResolution	VideoResolutionStruct				M
0x04	Quality	uint8	1 to 100			M
0x05	WatermarkEnabled	bool	all			WMARK
0x06	OSDEnabled	bool	all			OSD

11.2.8.8.1. ImageCodec Field

This field SHALL indicate the type of image codec to be used by the allocated snapshot stream as described in [ImageCodecEnum](#).

11.2.8.8.2. MaxFrameRate Field

This field SHALL indicate the maximum frame rate in frames per second of the allocated snapshot stream.

11.2.8.8.3. MinResolution Field

This field SHALL indicate the minimum resolution of the allocated snapshot stream.

11.2.8.8.4. MaxResolution Field

This field SHALL indicate the maximum resolution of the allocated snapshot stream.