

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	SnapshotStreamID	SnapshotStreamID-Type	all			M

11.2.8.9.1. SnapshotStreamID Field

The SnapshotStreamID field SHALL be an unsigned 16 bit integer representing the unique snapshot stream identifier.

11.2.8.10. SnapshotStreamDeallocate Command

This command SHALL deallocate an snapshot stream on the camera, corresponding to the given snapshot stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	SnapshotStreamID	SnapshotStreamID-Type	all			M

11.2.8.10.1. SnapshotStreamID Field

The SnapshotStreamID field SHALL be an unsigned 16 bit integer representing the unique snapshot stream identifier for the stream that needs to be deallocated.

11.2.8.10.2. Effect on Receipt

The process below SHALL be followed by the camera when receiving this command:

- If the SnapshotStreamID does not match an entry in [AllocatedSnapshotStreams](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the reference count for the stream with SnapshotStreamID is greater than 0:
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- Deallocate the snapshot stream with SnapshotStreamID.
- Remove the entry for SnapshotStreamID from [AllocatedSnapshotStreams](#).
- Respond with the status code SUCCESS.

11.2.8.11. SnapshotStreamModify Command

This command SHALL be used to modify a stream specified by the VideoStreamID.