

11.4.4.2. CTR Handling

Providers involved in an SFrame enabled WebRTC sessions SHALL utilize a single session-wide CTR value space that starts at 0 for each session. The CTR value SHALL increment by one for every new frame transmitted on any media line or Data Channel. Since the CTR values increase by one for each frame sent over any transport, the CTR could be non-monotonic for any given stream and SHOULD NOT be used for any packet loss detection. Providers SHALL NOT use any CTR values greater than $2^{63} - 1$.

Requestors SHALL use 64 bit CTR values in the range of 2^{63} and $2^{64} - 1$. Ecosystems need to ensure that each participant on the far end of a SFU uses a random starting CTR value within this range.

11.4.4.3. Packetization Mode

Nodes SHALL use the "per frame" mode of SFrame operation as defined in Section 4.1 of [RFC 9605](#).

11.4.4.4. Key-frame Handling

When SFrame is used, Nodes SHALL include the "Short Extension for Non-Scalable Streams" RTP header extension as defined in [RFC 9626](#) Section 3.2, for all non-discardable key-frames transmitted. This extension SHALL NOT be included for non key-frames.

11.4.5. Data Types

11.4.5.1. WebRTCSessionID Type

This data type is derived from uint16.

It represents an active WebRTC session. This value starts at 0 and monotonically increases by 1 with each new allocation provisioned by the Node. A value incremented past 65534 SHALL wrap to 0. The Node SHALL verify that the incremented ID does not match any other active session ID. If such a match is found, the ID SHALL be incremented until a unique ID is found.

11.4.5.2. WebRTCEndReasonEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	ICEFailed	No media connection could be established to the other party	M
1	ICETimeout	The call timed out whilst waiting for ICE candidate gathering to complete	M
2	UserHangup	The user chose to end the call	M