

Access Modifier: Fabric Scoped							
2	PeerEnd-pointID	endpoint-no	all				M
3	StreamUsage	StreamUsageEnum	all				M
4	VideoStreamID	VideoStreamIDType	all	X			M
5	AudioStreamID	AudioStreamIDType	all	X			M
6	MetadataEnabled	bool	all				M

This values of PeerNodeID and FabricIndex are used to validate the source of, or select the correct remote target, for WebRTC session related commands. The implicit field FabricIndex exists since this structure is defined as Fabric Scoped.

11.4.5.5.1. ID Field

This field contains the WebRTC Session ID for this session.

11.4.5.5.2. PeerNodeID Field

This field contains the NodeId for the peer entity involved in this session.

11.4.5.5.3. PeerEndpointID Field

This field contains the EndpointId for the peer entity involved in this session.

11.4.5.5.4. StreamUsage Field

This field contains the [StreamUsageEnum](#) of this session.

11.4.5.5.5. VideoStreamID Field

This field contains the [VideoStreamIDType](#) that is used by this session. A null value means no video stream is currently associated with this session.

11.4.5.5.6. AudioStreamID Field

This field contains the [AudioStreamIDType](#) that is used by this session. A null value means no audio stream is currently associated with this session.

11.4.5.5.7. MetadataEnabled Field

This field indicates if [metadata](#) is active in this session.