

11.5.5. Data Types

11.5.5.1. SFrameStruct Type

This type SHALL specify the [RFC 9605](#) data needed to use [SFrames](#) as an end-to-end encryption mechanism with WebRTC.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Cipher-Suite	uint16	min 1				M
1	BaseKey	octstr	max 128				M
2	KID	octstr	2 to 8				M

11.5.5.1.1. CipherSuite Field

This field SHALL specify the SFrame cipher suite value as defined in [RFC 9605](#) Section 8.1 Cipher Suites table, and maintained in the IANA [SFrame Registry](#) [<https://www.iana.org/assignments/sframe/sframe.xhtml>].

11.5.5.1.2. BaseKey Field

This field SHALL specify the SFrame base_key value to use for a session. The length of this key depends on the selected cipher suite's Nk value as defined in [Section 4.5 Cipher Suites](#) [<https://www.rfc-editor.org/rfc/rfc9605.html#name-cipher-suites>].

11.5.5.1.3. KID Field

This field SHALL specify the initial SFrame KID (Key Id) value to be used. The bottom 8 bits of this value will be overwritten and used for ratchet step tracking.

11.5.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	CurrentSessions	list[WebRTCSessionStruct]	all			R M S	M

11.5.6.1. CurrentSessions Attribute

This attribute SHALL be a list of [WebRTCSessionStruct](#), which represents all the active WebRTC Sessions.

11.5.7. Commands