

- If *AudioStreamID* is present and is null:
 - Automatically select an existing [audio stream](#) per the [Resource Management and Stream Priorities](#).
 - Store the used *AudioStreamID* in the *WebRTCSessionStruct*
- If not able to meet the [Resource Management and Stream Priorities](#) conditions or unable to provide another WebRTC session:
 - Invoke [End](#) with Reason set to *OutOfResources*, and end processing with no other side effects.
- Internally increment the [ReferenceCount](#) on any used video streams.
- Internally increment the [ReferenceCount](#) on any used audio streams.
- Store the *WebRTCSessionStruct* in the [CurrentSessions](#)
- Generate the SDP Offer and invoke [Offer](#), and if the passed in *ICEServers* and *ICETransportPolicy* were present, include those fields in the command.

11.5.7.2. SolicitOfferResponse Command

This command SHALL be generated in response to a [SolicitOffer](#) command.

This response contains information about the session and streams created and/or if a deferred offer will take place.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	DeferredOffer	bool	all			M
2	VideoStreamID	VideoStreamIDType	all	X		SolicitOffer.VideoStreamID
3	AudioStreamID	AudioStreamIDType	all	X		SolicitOffer.AudioStreamID

Upon receipt, the client SHALL create a new [WebRTCSessionStruct](#) populated with the values from this command, along with the accessing Peer Node ID and Local Fabric Index entries stored in the Secure Session Context as the *PeerNodeID* and *FabricIndex* values, and store it in the WebRTC Transport Requestor cluster's [CurrentSessions](#) attribute.

The session establishment SHALL be considered failed unless a [Offer](#) command is received by the Requestor from the [PeerEndpointID](#) / *FabricIndex* within 30 seconds.