

11.5.7.2.1. WebRTCSessionID Field

This field SHALL contain the ID of the established WebRTC session.

11.5.7.2.2. DeferredOffer Field

This field SHALL indicate the delayed processing hint of the provider.

If DeferredOffer is FALSE, the VideoStreamID and AudioStreamID fields SHALL NOT be null in this response and the Provider will without delay invoke the [Offer](#) command. If DeferredOffer is TRUE, the VideoStreamID and AudioStreamID fields MAY be non-null in this response, if the stream mapping logic can be done while in its low-power state, or they MAY be null, if it cannot. When TRUE, this is a hint to the Requestor that there will be a larger than normal amount of time before the [Offer](#) command will be invoked and the Requestor SHOULD use this extra time gap to begin its own ICE Candidate generation until the Offer arrives. (See further details in the section [WebRTC Battery Camera in Standby Flow](#))

11.5.7.2.3. VideoStreamID Field

This field SHALL contain the [VideoStreamIDType](#) used for the session if known or null if unknown at this time.

11.5.7.2.4. AudioStreamID Field

This field SHALL contain the [AudioStreamIDType](#) used for the session if known or null if unknown at this time.

11.5.7.3. ProvideOffer Command

This command allows an SDP Offer to be set and start a new session. This command can also be used in the re-offer flow of an existing session to change the details of the SDP (e.g. to enable/disable two-way talk).

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all	X		M
1	SDP	string	all			M
2	StreamUsage	StreamUsageEnum	all			M
3	OriginatingEndpointID	endpoint-no	all			M
4	VideoStreamID	VideoStreamIDType	all	X		O.c+