

Secure Channel, Secure Session Context section, in [MatterCore]) as the [PeerNodeID](#). The [PeerNodeID](#), [PeerEndpointID](#) and the associated fabric, SHALL be used as the destination for all asynchronous commands for the corresponding [WebRTCSessionID](#).

- Internally increment the [ReferenceCount](#) on any used video streams.
- Internally increment the [ReferenceCount](#) on any used audio streams.
- Store the [WebRTCSessionStruct](#) in the [CurrentSessions](#)
- Else:
 - If the accessing Peer Node ID stored in the Secure Session Context and the accessing fabric do not match the [PeerNodeID](#) and associated fabric for the [WebRTCSessionID](#) entry in [CurrentSessions](#):
 - Respond with a response status of NOT_FOUND
- Respond with a [ProvideOfferResponse](#)
- Process the SDP Offer, begin the ICE Candidate gathering phase, create the SDP Answer, and invoke [Answer](#) on the sessions [PeerEndpointID](#) / FabricIndex

11.5.7.4. ProvideOfferResponse Command

This command contains information about the session and streams created as a response to the requestor's offer.

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	VideoStreamID	VideoStreamIDType	all	X		WebRTCProvideOffer.VideoStreamID
2	AudioStreamID	AudioStreamIDType	all	X		WebRTCProvideOffer.AudioStreamID

Upon receipt, the client SHALL create a new [WebRTCSessionStruct](#) populated with the values from this command, along with the accessing Peer Node ID and Local Fabric Index entries stored in the Secure Session Context as the [PeerNodeID](#) and [FabricIndex](#) values, and store it in the WebRTC Transport Requestor cluster's [CurrentSessions](#) attribute.

11.5.7.4.1. WebRTCSessionID Field

This field SHALL contain the [WebRTCSessionID](#) of the established WebRTC session.