

the associated fabric and [PeerNodeID](#) field of the *WebRTCSessionID* entry in [CurrentSessions](#):

- Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- Internally decrement the [ReferenceCount](#) on any used video streams.
- Internally decrement the [ReferenceCount](#) on any used audio streams.
- Remove the entry in the [CurrentSessions](#) for *WebRTCSessionID*.

11.6. WebRTC Transport Requestor Cluster

The WebRTC transport requestor cluster provides a way for stream consumers (e.g. Matter Stream Viewer) to establish a WebRTC connection with a stream provider that implements the [WebRTC Transport Provider Cluster](#).

11.6.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial version of the WebRTC Transport Requestor Cluster

11.6.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	WEBRTCR

11.6.3. Cluster ID

ID	Name
0x0554	WebRTC Transport Requestor

11.6.4. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	CurrentSessions	list[WebRTCSessionStruct]	all			R A S	M

11.6.4.1. CurrentSessions Attribute

This attribute SHALL be a list of [WebRTCSessionStruct](#), which represents all the active WebRTC Sessions on this Node.