

- Respond with a response status of NOT_FOUND
- Remove the entry in the [CurrentSessions](#) for WebRTCSessionID

11.7. Push AV Stream Transport Cluster

This cluster implements the upload of Audio and Video streams from the [Camera AV Stream Management Cluster](#) using suitable push-based transports. Push AV Stream Transport is the transmission of a stream of media to a server, initiated by the activation of an associated trigger. A push transport can be triggered from a camera operating in an always-on mode for supporting 24/7 style recording, triggered by events based on motion zones defined in the [Zone Management Cluster](#), or manually triggered using commands or bindings.

A push transport SHALL be allocated before it is intended to be used, and then it is subsequently started when its configured trigger is activated.

An allocated push transport consists of five main logical things:

- A container format, which specifies how the individual media frames are formatted or multiplexed together
- An ingestion format which specifies how it is signaled and transmitted to the far end.
- A trigger which specifies when transport will occur.
- Which media stream/s to package together in the container format.
- Various options to the above.

All push transport [ingest methods](#) SHALL use TLS as specified by the core specification. TLS Client Certificates SHALL be used for Authorization and Identification of a Node on the underlying TLS connection (see Chapter 14, TLS Certificate Management and TLS Client Management sections in [\[MatterCore\]](#)). Nodes supporting this cluster SHALL also support the TLS Client Management Cluster and its dependencies.

11.7.1. CMAF Ingestion

CMAF Ingestion as defined in [DASH-IF Live Media Ingest Protocol](#) version 1.2 and newer SHALL be supported.

Nodes SHALL support both [Interface-1: CMAF Ingest](#) [<https://dashif.org/Ingest/#interface-1>] and [Interface-2: DASH and HLS Ingest](#) [<https://dashif.org/Ingest/#interface-2>].

Nodes SHALL use [HTTP/2](#) or newer, for all CMAF Ingestion HTTP based operations.

Nodes using [CMAFIngest](#) as the ingestion method SHALL use [CMAF](#) as the [container format](#).

11.7.1.1. Background

The Matter Node is considered the CMAF [ingest source](#) [<https://dashif.org/Ingest/#ingest-source>]. The CMAF [receiving-entity](#) [<https://dashif.org/Ingest/#receiving-entity>] is the server that the Matter Node will send the media stream to. The receiving-entity details along with the media streams that make up the [ingest-stream](#) [<https://dashif.org/Ingest/#ingest-stream>] are provisioned in a [TransportOptionsStruct](#).