

with a URL forward slash character `/`. The `publishing_point_URL` MAY contain as many URL path components as fit within the allocated space of the `URL` field. Any `publishing_point_URL` issued to a Matter device SHALL allow for one or more Sessions.

An example of a `publishing_point_url` is: `https://ingest.example.com/provider_supplied_arbitrary_data/in/base/part/of/url/`

The second component of the `POST_URL` is a dynamically computed string that includes the `Session` name, `Track` name, and `Segment` name. Each of these three values are placed in that order as extended paths at the end of the `publishing_point_URL`. The Session and Segment names also contain numerically increasing portions of their string, which allows for the receiving-entity to determine the event time bounds information along with the individual segment information.

An example of the second component is: `session_1/media1/segment_1001.m4s`. In this example, `session_1` is the session name, `media1` is the track name, and `segment_1001.m4s` is the segment name.

For Matter deployments, the extended path SHALL be comprised of the three elements in the following order: `session_name/track_name/segment_name` and each sub-portion SHALL follow these rules:

`session_name`: Consists of the fixed value `session_` followed by a monotonically increasing *SessionNumber* numeric string managed by this cluster. *SessionNumber* SHALL be of type `uint64` and start with value 1 when a transport is first allocated.

`track_name`: Consists of a provisioned string provided in the `TrackName` field.

`segment_name`: Consists of the fixed value `segment_` followed by a monotonically increasing *SegmentNumber* numeric string managed by this cluster, followed by a period `.`, followed by the media type's `Segment Extension`.

When the fixed and variable pieces are put together the extended paths are: `session_<SessionNumber>/<TrackName>/segment_<SegmentNumber>.<SegmentExtension>`

11.7.1.3. Segment Numbering

In Matter's usage of CMAF, *SegmentNumber* SHALL be of type `uint16` and start at 1001 for each `Track` within each `Session`. In practice, a *SegmentNumber* will likely never exceed 9999 due to the Session length duration limit.

11.7.1.4. Segment Extension

In Matter's usage of CMAF, the following table SHALL determine the value for *SegmentExtension*:

Extension	Mime-Type	Usage
m4s	video/iso.segment	When the track contains video or audio

11.7.1.5. Track Naming

When using an interleaved transport where both `VideoStreamID` and `AudioStreamID` are populated