

11.7.6.7. CMAFInterfaceEnum Type

This data type is derived from enum8. This type indicates the exact mode of CMAF that is in use.

Value	Name	Summary	Conformance
0	Interface1	CMAF Interface-1 Mode	M
1	Interface2DASH	CMAF Interface-2 Mode with DASH Support	P, M
2	Interface2HLS	CMAF Interface-2 Mode with HLS Support	P, M

11.7.6.7.1. Interface1 Value

This value indicates that only the operations specified in [CMAF Interface-1](https://dashif.org/Ingest/#interface-1) [https://dashif.org/Ingest/#interface-1] will be done.

11.7.6.7.2. Interface2DASH Value

This value indicates the operations specified in [CMAF Interface-2](https://dashif.org/Ingest/#interface-2) [https://dashif.org/Ingest/#interface-2] with the [DASH specific portions](https://dashif.org/Ingest/#dash-ingest-requirements) [https://dashif.org/Ingest/#dash-ingest-requirements] will be done.

11.7.6.7.3. Interface2HLS Value

This value indicates the operations specified in [CMAF Interface-2](https://dashif.org/Ingest/#interface-2) [https://dashif.org/Ingest/#interface-2] with the [HLS specific portions](https://dashif.org/Ingest/#hls-ingest-requirements) [https://dashif.org/Ingest/#hls-ingest-requirements] will be done.

11.7.6.8. CMAFContainerOptionsStruct Type

This struct encodes options for configuration of the CMAF container format.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	CMAFInterface	CMAFInterfaceEnum	all				M
1	SegmentDuration	uint16	500 to 65500				M
2	ChunkDuration	uint16	0 to (SegmentDuration/2)				M
3	SessionGroup	uint8	all				M
4	TrackName	string	1 to 16				M
5	CENCKey	octstr	16				P, O