

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
8	Expiry-Time	epoch-s	all				O

11.7.6.13.1. StreamUsage Field

This field contains the [StreamUsageEnum](#) of this transport.

11.7.6.13.2. VideoStreamID Field

This field SHALL have the following semantics:

- If not present, video isn't requested.
- If present and null, automatic video stream assignment is requested.
- If present and non-null, the specific video stream identified by the [VideoStreamIDType](#) is requested.

11.7.6.13.3. AudioStreamID Field

This field SHALL have the following semantics:

- If not present, audio isn't requested.
- If present and null, automatic audio stream assignment is requested.
- If present and non-null, the specific audio stream identified by the [AudioStreamIDType](#) is requested.

11.7.6.13.4. TLSEndpointID Field

This field SHALL be a TLSEndpointID representing a provisioned TLS Endpoint, which SHALL have valid TLSCAID and TLSCCID values (see Chapter 14, Certificate Authority ID (CAID) Mapping and the ProvisionEndpoint command in the TLS Client Management Cluster sections in [\[MatterCore\]](#)).

11.7.6.13.5. URL Field

This field SHALL be a valid string in [RFC 3986](#) format representing the upload location. The field SHALL use the [https](#) scheme which will be validated by the underlying TLSEndpointID.

When the IngestMethod is CMAFIngest, this SHALL be the CMAF [publishing_point_URL](#) [https://dashif.org/Ingest/#publishing_point_url] to transport the AV Stream to. The URL length does not need to include space for the full CMAF POST_URL fields which specify the session, track, and segment names as these will be internally appended.

11.7.6.13.6. TriggerOptions Field

This field SHALL be of type [TransportTriggerOptionsStruct](#) and represents the Trigger Type and its sub options.