

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	SupportedFormats	list[SupportedFormatStruct]	min 1	F		R V	M
0x0001	CurrentConnections	list[TransportConfigurationStruct]	desc	N		R V S	M

11.7.8.1. SupportedFormats Attribute

This attribute SHALL contain a list of [Supported Container Format](#) structs, which represents the combinations of Ingestion Method and Container Format that the Node supports. Nodes SHALL support at least the combination [CMAFIngest](#),[CMAF](#).

11.7.8.2. CurrentConnections Attribute

This attribute SHALL be a list of [TransportConfigurationStruct](#) which represents all the allocated connections added via [AllocatePushTransport](#). When this attribute is read over a non Large Message (See Large Message Quality in the Data Model section of [\[MatterCore\]](#)) capable transport, the TransportOptions field SHALL NOT be included. To get the full details of the connections use the [FindTransport](#) command. The maximum size of this list is run-time dependent upon the resource constraints of the system as described in [Resource Management and Stream Priorities](#) and the currently used bandwidth of the total available specified by [MaxNetworkBandwidth](#).

11.7.9. Commands

ID	Name	Direction	Response	Access	Quality	Conformance
0x00	AllocatePushTransport	client ⇒ server	AllocatePushTransportResponse	M F	L	M
0x01	AllocatePushTransportResponse	server ⇒ client	N		L	M
0x02	DeallocatePushTransport	client ⇒ server	Y	M F		M
0x03	ModifyPushTransport	client ⇒ server	Y	M F		M