

cessing with no other side effects.

- If the requested combination of [IngestMethod](#) and [ContainerType](#) from the [ContainerOptions](#) fields, of the passed in *TransportOptions*, is not in [SupportedFormats](#):
 - Fail the command with the cluster-specific status code of `InvalidCombination`, and end processing with no other side effects.
- If the URL is invalid:
 - Fail the command with the cluster-specific status code of `InvalidURL`, and end processing with no other side effects.
- If the [StreamUsage](#) field's value is not present in the [StreamUsagePriorities](#) list:
 - Fail the command with the cluster-specific status code of `InvalidStreamUsage`, and end processing with no other side effects.
- If the [MotionZones](#) field is present in the [TriggerOptions](#) field of *TransportOptions*:
 - If there are any entries with duplicate values for the [Zone](#) field in [MotionZones](#):
 - Fail the command with the status code `ALREADY_EXISTS`, and end processing with no other side effects.
 - If the length of the [MotionZones](#) list is greater than [MaxZones](#):
 - Fail the command with the status code `DYNAMIC_CONSTRAINT_ERROR`, and end processing with no other side effects.
 - If the [MotionZones](#) list in the [TriggerOptions](#) field of *TransportOptions* contains an invalid [ZoneID](#):
 - Fail the command with the cluster-specific status code of `InvalidZone`, and end processing with no other side effects.
- If this new transport would exceed the [bandwidth limits](#):
 - Fail the command with `RESOURCE_EXHAUSTED`, and end processing with no other side effects.
- If the [VideoStreamID](#) field of the passed in *TransportOptions* is present and null:
 - If [AllocatedVideoStreams](#) is empty:
 - Fail the command with the status code `INVALID_IN_STATE`, and end processing with no other side effects.
 - Automatically select an existing [video stream](#) per the [Resource Management and Stream Priorities](#).
 - Save the resulting [VideoStreamID](#) into the *TransportOptions*.
- If the [AudioStreamID](#) field of the passed in *TransportOptions* is present and null:
 - If [AllocatedAudioStreams](#) is empty:
 - Fail the command with the status code `INVALID_IN_STATE`, and end processing with no other side effects.
 - Automatically select an existing [audio stream](#) per the [Resource Management and Stream Priorities](#).