

11.8.3. Cluster ID

ID	Name
0x0556	Chime

11.8.4. Data Types

11.8.4.1. ChimeSoundStruct Type

This struct is used to encode information needed to define a Chime Sound.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	ChimeID	uint8	all				M
1	Name	string	1 to 48				M

11.8.4.1.1. ChimeID Field

This field SHALL represent the unique ID for a Chime sound.

11.8.4.1.2. Name Field

This field SHALL represent the unique user friendly name of the Chime Sound.

11.8.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Installed-Chime-Sounds	list[Chime-Sound]	1 to 255	F		R V	M
0x0001	Selected-Chime	uint8	all	N		RW VO	M
0x0002	Enabled	bool	all	N		RW VO	M

11.8.5.1. InstalledChimeSounds Attribute

This attribute SHALL contain all installed chime sounds, represented by a list of [Chime Sounds](#). Each entry in this list SHALL have a unique [ChimeID](#) value and a unique [Name](#) value.

11.8.5.2. SelectedChime Attribute

This attribute SHALL indicate the currently selected chime sound that will be played when [Play-ChimeSound](#) is invoked and SHALL be the [ChimeID](#) value for the requested Chime Sound within [InstalledChimeSounds](#).

This attribute MAY be written by the client to request a different chime sound. An attempt to write