

Class Tag	Summary
Composed	the device type is composed of 2 or more device types (see System Model specification)

1.1.6. Endpoint Type Class Conditions

This category is for classifications of endpoints. Some of these classifications are dependent on other conditions.

Class Tag	Summary
Client	there exists a client application cluster on the endpoint
Server	there exists a server application cluster on the endpoint
Duplicate	the endpoint and at least one of its siblings have overlap in application device type(s)
BridgedPowerSourceInfo	the endpoint represents a Bridged Device, for which information about the state of its power source is available to the Bridge

1.1.6.1. Duplicate Condition

The endpoint and at least one of its sibling endpoints have an overlap in application device type(s), as defined in the "Disambiguation" section in the System Model specification. This condition triggers requirements for providing additional information about the endpoints in order to disambiguate between the endpoints (see "Disambiguation" section in the System Model specification).

1.1.7. Cluster Requirements

Each Matter device type implementation SHALL include these clusters, as a minimum set, based on the conformance defined below. This conformance table SHALL assume the Matter conformance condition is TRUE (in Conformance column).

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x001D	Descriptor	Server		M
0x001E	Binding	Server		Simple & Client
0x0040	Fixed Label	Server		O
0x0041	User Label	Server		O

1.1.8. Element Requirements

The table below lists qualities and conformance that override the cluster specification requirements. A blank entry means no change.