

2.1.2. Classification

Device Type ID	Device Type Name	Superset Of	Class	Scope
0x0016	Root Node		Node	Node

2.1.3. Conditions

The following table lists conditions that MAY be defined for this device type. This is used by device types which need certain clusters or features thereof to be present on this device type (Root Node). See [Section 1.1.3, “Base Type Conditions”](#) for additional conformance tags.

Condition	Description
CustomNetworkConfig	The node only supports out-of-band-configured networking (e.g. rich user interface, manufacturer-specific means, custom commissioning flows, or future IP-compliant network technology not yet directly supported by NetworkCommissioning cluster).
ManagedAclAllowed	The node has at least one endpoint where some Device Type present on the endpoint has a Device Library element requirement table entry that sets this condition to true.
TimeSyncCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use Time Synchronization support.
TimeSyncWithClientCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use Time Synchronization support with Client cluster support, and the TimeSyncClient feature.
TimeSyncWithNTPCCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use Time Synchronization support with the NTP-Client feature.
TimeSyncWithTZCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use Time Synchronization support with the TimeZone feature.
TLSCertificatesCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use TLS Certificate Management. Since TLS requires basic Time Sync support, this will include that dependency.