

Cluster ID	Cluster Name	Element	Name	Constraint	Access	Conformance
0x0098	Device Energy Management	Feature	PowerAdjustment			[Control-lableESA].a+
0x0098	Device Energy Management	Feature	StartTimeAdjustment			[Control-lableESA].a+
0x0098	Device Energy Management	Feature	Pausable			[Control-lableESA].a+
0x0098	Device Energy Management	Feature	ForecastAdjustment			[Control-lableESA].a+
0x0098	Device Energy Management	Feature	Constraint-BasedAdjustment			[Control-lableESA].a+

2.8. Secondary Network Interface Device Type

A Secondary Network Interface device provides an additional network interface supported by the Node, supplementing the primary interface hosted by the Root Node endpoint.

A Node supporting multiple network interfaces SHALL include the primary interface on the Root Node endpoint, along with secondary interfaces on other endpoints. The priorities of these network interfaces are determined by the order of their endpoints, where interfaces with smaller endpoint numbers are higher priority.

2.8.1. Revision History

Revision	Description
1	Initial revision

2.8.2. Classification

Device Type ID	Device Type Name	Superset Of	Class	Scope
0x0019	Secondary Network Interface		Utility	Endpoint

2.8.3. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.