

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x0004	Groups	Client		O
0x0006	On/Off	Client		M
0x0008	Level Control	Client		M
0x0062	Scenes Management	Client		O
0x0300	Color Control	Client		M

6.4. Control Bridge Device Type

A Control Bridge is a controller device that, when bound to a lighting device such as an Extended Color Light, is capable of being used to switch the device on or off, adjust the intensity of the light being emitted and adjust the color of the light being emitted. In addition, a Control Bridge device is capable of being used for setting scenes.

6.4.1. Revision History

Revision	Description
1	Initial Zigbee 3.0 revision
2	New data model format and notation
3	Updated the Scenes cluster to Scenes Management with Cluster ID: 0x0062

6.4.2. Classification

Device Type ID	Device Type Name	Superset Of	Class	Scope
0x0840	Control Bridge		Simple	Endpoint

6.4.3. Conditions

See the Base Device Type definition for conformance tags.

6.4.4. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.

Table 8. Control Bridge Cluster Requirements

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x0003	Identify	Server		M
0x0003	Identify	Client		M