

To identify the location of a button on the device (e.g. top button of a two-button device), the semantic tags from the Common Position Namespace SHALL be used where applicable.

For devices where these are not applicable or not sufficient (e.g. a switch device with four buttons in a row), the semantic tags from the Common Number Namespace SHALL be used to enumerate the position of the buttons on the device, in left to right, top to bottom order, starting with **Number.One** for the first button.

For devices to control a Closure (e.g. Window Covering), the semantic tags from the Switches Namespace SHALL be used where applicable.

Example 1: a device with two rocker switches (mounted side by side), which has two endpoints (11,12) for the switch-related functionality

- endpoint 11 has device type Generic Switch and contains
  - cluster Switch (feature flags: LS) exposing the state and events of the left button
  - cluster Descriptor with its TagList containing two tags: **Position.Left** and **Number.One**
- endpoint 12 has device type Generic Switch and contains
  - cluster Switch (feature flags: LS) exposing the state and events of the right button
  - cluster Descriptor with its TagList containing two tags: **Position.Right** and **Number.Two**

If this device were to have labeling on the buttons like an "up" and "down" icon, the TagList would have a third tag (from the Switches Namespace) with values **Switches.Up** and **Switches.Down** respectively.

Example 2: a device with four push buttons (mounted in a square), each labeled with an icon for a certain scene setting, which has four endpoints (21,22,23,24) for the switch-related functionality

- endpoint 21 has device type Generic Switch and contains
  - cluster Switch (feature flags: MS) exposing the events of the top-left button
  - cluster Descriptor with its TagList containing four tags: **Position.Top**, **Position.Left**, **Number.One** and (Tag=**Switches.Custom**, Label="watch tv")
    - This last tag is a **Switches.Custom** tag accompanied with a label (the other three tags do not need a Label field).
- endpoint 22 has device type Generic Switch and contains
  - cluster Switch (feature flags: MS) exposing the events of the top-right button
  - cluster Descriptor with its TagList containing four tags: **Position.Top**, **Position.Right**, **Number.Two** and (Tag=**Switches.Custom**, Label="dinner")
- endpoint 23 has device type Generic Switch and contains
  - cluster Switch (feature flags: MS) exposing the events of the bottom-left button
  - cluster Descriptor with its TagList containing four tags: **Position.Bottom**, **Position.Left**, **Number.Three** and (Tag=**Switches.Custom**, Label="reading")
- endpoint 24 has device type Generic Switch and contains