

App upon commands targeted to a Content App endpoint.

The following steps are performed by a Casting Video Player when granting and removing Client access to Content App endpoints:

1. Upon commissioning a Client and granting it access to a Content App endpoint, the Casting Video Player SHALL invoke the Login command of the AccountLogin cluster on the Content App endpoint (when implemented by the Content App) in order to notify the Content App endpoint of the Client.
 - a. If the Client is a Casting Video Client and it implements the Content App Observer server cluster, and if the Content App endpoint implements both the Binding server cluster and the Content App Observer client cluster, then the Casting Video Player SHALL create a binding on the Content App endpoint which specifies the Node and Endpoint of the Casting Video Client's Content App Observer server cluster. The Casting Video Player SHALL provide a way for the Content App to send a Content App Observer cluster ContentAppMessage command to the Casting Video Client and to receive a ContentAppMessageResponse in return.
2. Upon removing access to a Content App endpoint for a Client, the Casting Video Player SHALL invoke the Logout command of the AccountLogin cluster on the Content App endpoint (when implemented by the Content App) in order to notify the Content App endpoint that Client access has been removed.
 - a. If the Casting Video Player created a binding on the Content App endpoint corresponding to the Casting Video Client's Content App Observer server cluster, then the Casting Video Player SHALL remove this binding.

When the Content App endpoint generates a LoggedOut event, the Casting Video Player SHALL remove access to the Node specified to the given Content App endpoint.

NOTE

A Client commissioned by the Casting Video Player is able to determine if the corresponding Content App is visible to the user using the **Status** attribute on the Application Basic cluster for the Content App endpoint. This ensures that the Client cannot access foreground Content App information about any other Content App to which it does not have access. It also ensures that such a client will only need access to specific Content App endpoints and the Speaker endpoint (when present).

10.1.5. Determining Context

A client that controls multiple aspects of the Video Player functionality (like a voice assistant) may have access to multiple endpoints on the Video Player. To determine the current context on the Video Player when the user interacts with the client (for example, when the user interacts with the device using voice), the client can look at the state in the various clusters on the Casting Video Player.

Specifically:

1. Media Input cluster (when CurrentInput does NOT have type INTERNAL, then Video Player is displaying content from a physical input)
2. Application Launcher cluster (CurrentApp indicates the current application endpoint - which