

# Chapter 11. Generic Device Types

## 11.1. Mode Select Device Type

This defines conformance to the Mode Select device type.

### 11.1.1. Revision History

| Revision | Description      |
|----------|------------------|
| 1        | Initial revision |

### 11.1.2. Classification

| Device Type ID | Device Type Name | Superset Of | Class  | Scope    |
|----------------|------------------|-------------|--------|----------|
| 0x0027         | Mode Select      |             | Simple | Endpoint |

### 11.1.3. Conditions

See the Base Device Type definition for conformance tags.

### 11.1.4. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.

| Cluster ID | Cluster Name | Client/Server | Quality | Conformance |
|------------|--------------|---------------|---------|-------------|
| 0x0050     | Mode Select  | Server        |         | M           |

## 11.2. Aggregator Device Type

This device type aggregates endpoints as a collection. Clusters on the endpoint indicating this device type provide functionality for the collection of descendant endpoints present in the PartsList of the endpoint's descriptor, for example the Actions cluster.

The purpose of this device type is to aggregate functionality for a collection of endpoints. The definition of the collection or functionality is not defined here.

When using this device type as a collection of bridged nodes, please see the "Bridge" section in the System Model specification.

### 11.2.1. Revision History