

EP0 – Root Node
 DeviceTypeList: [RootNode]
 PartsList: [11,12,13,14, 21,22,23, 31,32,33]

EP11 – aggregator for the bridged Zigbee devices
 DeviceTypeList: [**Aggregator**]
 PartsList: [12,13,14, 21,22,23]

EP12 – bridged Zigbee (white) light
 DeviceTypeList: [Bridged Node, Dimmable Light]
 PartsList: []

EP13 – bridged Zigbee (color) light
 DeviceTypeList: [Bridged Node, Extended Color Light]
 PartsList: []

EP14 – bridged Zigbee device which bridges to a series of DALI lights
 DeviceTypeList: [Bridged Node, **Aggregator**]
 PartsList: [21,22,23]

EP21 – DALI light
 DeviceTypeList: [Bridged Node, Dimmable Light]
 PartsList: []

EP22 – DALI light
 DeviceTypeList: [Bridged Node, Dimmable Light]
 PartsList: []

EP23 – DALI light
 DeviceTypeList: [Bridged Node, Dimmable Light]
 PartsList: []

Zigbee devices exposed via Aggregator on EP11 (including the DALI lights EP 21-23)

DALI devices exposed via Aggregator on EP14

EP31 – aggregator for the bridged Z-Wave devices
 DeviceTypeList: [**Aggregator**]
 PartsList: [32,33]

EP32 – bridged Z-Wave (white) light
 DeviceTypeList: [Bridged Node, Dimmable Light]
 PartsList: []

EP33 – bridged Z-Wave (color) light
 DeviceTypeList: [Bridged Node, Extended Color Light]
 PartsList: []

Z-Wave devices exposed via Aggregator on EP31

Figure 9. examples of multiple aggregators

11.2.6. Disambiguation

If the Duplicate condition applies to child endpoints of an Aggregator endpoint that represent multiple independent bridged devices, the endpoints SHOULD make available metadata to allow a client to disambiguate distinct bridged devices with an overlap in application device types.

Typically this is done using the NodeLabel attribute of the Bridged Device Basic Information cluster