

13.5.4. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.

ID	Cluster	Client/Server	Conformance
0x0003	Identify	Server	O
0x0006	On/Off	Server	O
0x0056	Temperature Control	Server	O
0x0059	Dishwasher Mode	Server	O
0x005D	Dishwasher Alarm	Server	O
0x0060	Operational State	Server	M

NOTE

A dishwasher cycle is a combination of a mode (if supported) and a temperature (if supported). The operational state cluster is then used to start the cycle once these selections have been made via the client.

13.5.5. Cluster Restrictions

13.5.5.1. Temperature Control Cluster (Server) Clarifications

Given that different markets have different customary methods of providing temperature settings (e.g. North America often prefers levels, whereas many other markets provide temperatures in °C), it is RECOMMENDED that when the Temperature Control cluster is present, the TemperatureLevel or TemperatureNumber feature of that cluster is chosen to follow the most widely applied convention for the market where the product is sold.

13.5.5.2. On/Off Cluster (Server) Clarifications

As indicated in the Element Requirements section below, the DF (Dead Front) feature is required for the On/Off cluster in this device type. See the "DeadFrontBehavior feature" section in the On/Off cluster description for detailed requirements. The "dead front" state is linked to the OnOff attribute in the On/Off cluster having the value False. Thus, the Off command of the On/Off cluster SHALL move the device into the "dead front" state, the On command of the On/Off cluster SHALL bring the device out of the "dead front" state, and the device SHALL adhere with the associated requirements on subscription handling and event reporting.

13.5.5.3. Best Effort Attribute Values in "Dead Front" State

When in "dead front", should the operational values of the cluster attributes not be available or accessible, the following are the RECOMMENDED best effort values for per cluster attributes when responding to a new subscription request or a read request. Attributes not listed have no change in their defined or expected values.