

Chapter 9. Common Position Semantic Tag Namespace

This section contains the Common Position semantic tag namespace as part of the semantic tag feature.

The tags contained in this namespace MAY be used in any domain or context, to indicate an association with a position relative to the device (e.g. the temperature sensor in the top drawer of a refrigerator, or location of the buttons on a multi-button switch device). Note the difference with [Chapter 5, Common Direction Semantic Tag Namespace](#).

ID	Namespace
0x08	Common Position

The following tags are defined in this namespace.

ID	Name	Summary
0x00	Left	
0x01	Right	
0x02	Top	
0x03	Bottom	
0x04	Middle	
0x05	Row	Numeric value provided in Label field
0x06	Column	Numeric value provided in Label field

When multiple endpoints are used for device types, and the associated consumer-facing locations of those endpoints are organized in a straight line, grid or matrix, these endpoints SHOULD be allocated in top-to-bottom, left-to-right order.

For grids or arrays larger than 3 elements in any direction, the Row and Column tags SHOULD be used.

If the Row or Column tags are used, the Label field in the same Semantic Tag structure SHALL be filled with a number comprised of Arabic numerals encoded as a string to indicate the row/column of the item. Number words (e.g. "one", "two", etc.) SHALL NOT be used to describe the position of the item. The first row/column SHALL use Label "1".

9.1. Examples

The following example illustrates a compound device comprised of 9 endpoints arranged in a 3x3 grid. This example uses position tags to indicate position.