

compound device arranged in a 3x3 grid

Top	Left	Top	Middle	Top	Right
Middle	Left	Middle		Middle	Right
Bottom	Left	Bottom	Middle	Bottom	Right

The endpoints would be populated in this order (showing the TagList in their Descriptor cluster):

- EP 21: Top Left
- EP 22: Top Middle
- EP 23: Top Right
- EP 24: Middle Left
- EP 25: Middle
- EP 26: Middle Right
- EP 27: Bottom Left
- EP 28: Bottom Middle
- EP 29: Bottom Right

The following example illustrates a compound device comprised of 8 endpoints arranged in a 2x4 grid. This example uses the Row and Column tags along with Arabic numeral Labels to indicate position.

Row "1" Column "1"	Row "1" Column "2"	Row "1" Column "3"	Row "1" Column "4"
Row "2" Column "1"	Row "2" Column "2"	Row "2" Column "3"	Row "2" Column "4"

The endpoints would be populated in this order (showing the TagList in their Descriptor cluster):

- EP 31: {Row, "1"}, {Column, "1"}
- EP 32: {Row, "1"}, {Column, "2"}
- EP 33: {Row, "1"}, {Column, "3"}
- EP 34: {Row, "1"}, {Column, "4"}
- EP 35: {Row, "2"}, {Column, "1"}
- EP 36: {Row, "2"}, {Column, "2"}
- EP 37: {Row, "2"}, {Column, "3"}
- EP 38: {Row, "2"}, {Column, "4"}