

Response Parameters

name	type	description
response_code	integer	0: Successful request / Others: Error Refer to " Response Code List " for details

Example Response	{ "response_code":0 }
------------------	-----------------------------

6.11. movePreset

For moving preset.

For example, if execute movePreset?from=4&to=2 for list {[A], [B], [C], [D], [E] ...}, list is arranged as {[A], [D], [B], [C], [E] ...}.

Request Parameters

name	type	required	description
band	string	yes	Specifies Band. Values depend on Preset Type gotten via /system/getFeatures Values: "common" (common), "am" / "fm" / "dab" (separate)
from	integer	yes	Specifies source preset number Values: one in the range gotten via /system/getFeatures
to	integer	yes	Specifies destination preset number Values: one in the range gotten via /system/getFeatures

URI	<BaseURL>/v1/tuner/movePreset?band=<band>&from=<from>&to=<to>
Method	GET
Example Request	http://{host}/YamahaExtendedControl/v1/tuner/movePreset?band=am&from=10&to=3

Response Parameters

name	type	description
response_code	integer	0: Successful request / Others: Error Refer to " Response Code List " for details

Example Response	{ "response_code":0 }
------------------	-----------------------------

6.12. startDabInitialScan

For starting DAB Initial Scan. Available only when " dab_initial_scan " exists in tuner - func_list under /system/getFeatures.

Request Parameters

URI	<BaseURL>/v1/tuner/startDabInitialScan
Method	GET
Example Request	http://{host}/YamahaExtendedControl/v1/tuner/startDabInitialScan