

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				B A																															
Reset 0x00100010				0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0																															
ID	R/W	Field	Value ID	Value	Description																														
A	RW	SECATTR			SECATTR feature																														
			NonSecure	0	Feature is available for non-secure usage																														
			Secure	1	Feature is reserved for secure usage																														
B	RW	LOCK W1S			LOCK feature																														
			Unlocked	0	Feature permissions can be updated																														
			Locked	1	Feature permissions can not be changed until the next reset																														
					When Locked, it remains Locked until the next reset cycle.																														

7.8.5.5.9 FEATURE.DPPIC.CHG[n] (n=0..7)

Address offset: 0x6E0 + (n × 0x4)

Security configuration for channel group n of DPPIC

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0				
ID																				B				A															
Reset 0x00100010				0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0			
ID	R/W	Field	Value ID	Value	Description																																		
A	RW	SECATTR			SECATTR feature																																		
			NonSecure	0	Feature is available for non-secure usage																																		
			Secure	1	Feature is reserved for secure usage																																		
B	RW	LOCK W1S			LOCK feature																																		
			Unlocked	0	Feature permissions can be updated																																		
			Locked	1	Feature permissions can not be changed until the next reset																																		
					When Locked, it remains Locked until the next reset cycle.																																		

7.8.5.5.10 FEATURE.GPIOTE[n].CH[o] (n=0..1) (o=0..7)

Address offset: 0x700 + (n × 0x40) + (o × 0x4)

Security configuration for channel o of GPIOTE[n]

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0												
ID																												B				A															
Reset 0x00100010				0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0										
ID	R/W	Field	Value ID	Value		Description																																									
A	RW	SECATTR				SECATTR feature																																									
			NonSecure	0	Feature is available for non-secure usage																																										
			Secure	1	Feature is reserved for secure usage																																										
B	RW	LOCK W1S				LOCK feature																																									
			Unlocked	0	Feature permissions can be updated																																										
			Locked	1	Feature permissions can not be changed until the next reset																																										
			When Locked, it remains Locked until the next reset cycle.																																												

7.8.5.5.11 FEATURE.GPIOTE[n].INTERRUPT[o] (n=0..1) (o=0..7)

Address offset: 0x720 + (n × 0x40) + (o × 0x4)