

8.19.7 Low power. . . . .	587
8.19.8 Registers. . . . .	588
8.20 SPIS — Serial peripheral interface target with EasyDMA. . . . .	610
8.20.1 SPI modes. . . . .	611
8.20.2 Shared resources. . . . .	611
8.20.3 EasyDMA. . . . .	612
8.20.4 SPIS operation. . . . .	612
8.20.5 Semaphore operation. . . . .	614
8.20.6 Pin configuration. . . . .	615
8.20.7 Registers. . . . .	616
8.21 TEMP — Temperature sensor. . . . .	634
8.21.1 Operation. . . . .	635
8.21.2 Registers. . . . .	635
8.22 TIMER — Timer/counter. . . . .	643
8.22.1 Capture. . . . .	644
8.22.2 Compare. . . . .	644
8.22.3 Task delays. . . . .	645
8.22.4 Task priority. . . . .	645
8.22.5 Registers. . . . .	645
8.23 TWIM — I <sup>2</sup> C compatible two-wire interface controller with EasyDMA. . . . .	652
8.23.1 TWIM operation. . . . .	653
8.23.2 Shared resources. . . . .	654
8.23.3 EasyDMA. . . . .	654
8.23.4 TWIM write sequence. . . . .	654
8.23.5 TWIM read sequence. . . . .	655
8.23.6 TWIM repeated start sequence. . . . .	656
8.23.7 Low power. . . . .	657
8.23.8 TWIM pin configuration. . . . .	657
8.23.9 Pull-up resistor. . . . .	658
8.23.10 Registers. . . . .	659
8.24 TWIS — I <sup>2</sup> C compatible two-wire interface target with EasyDMA. . . . .	683
8.24.1 State machine. . . . .	684
8.24.2 Shared resources. . . . .	686
8.24.3 EasyDMA. . . . .	686
8.24.4 Read command response. . . . .	687
8.24.5 Write command response. . . . .	688
8.24.6 TWI controller repeated start sequence. . . . .	689
8.24.7 Terminate an ongoing TWI transaction. . . . .	690
8.24.8 Low power. . . . .	690
8.24.9 Target mode pin configuration. . . . .	690
8.24.10 Registers. . . . .	691
8.25 UARTE — Universal asynchronous receiver/transmitter with EasyDMA. . . . .	713
8.25.1 Baudrate. . . . .	714
8.25.2 EasyDMA. . . . .	714
8.25.3 Transmission. . . . .	715
8.25.4 Reception. . . . .	715
8.25.5 Data frame size. . . . .	717
8.25.6 Frame timeout interrupt. . . . .	718
8.25.7 Error conditions. . . . .	719
8.25.8 Using the UARTE without flow control. . . . .	719
8.25.9 Parity and stop bit configuration. . . . .	719
8.25.10 Compare match filter. . . . .	720
8.25.11 Low power. . . . .	720
8.25.12 Pin configuration. . . . .	720