

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				O N M L K J I H G F																E D C				B				A							
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value	Description																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														
H	RW	DMARXBUSERROR			Enable or disable interrupt for event DMARXBUSERROR																														
					When this event is generated, the address which caused the error can be read from the BUSERRORADDRESS register.																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														
I-L	RW	DMARXMATCH[i] (i=0..3)			Enable or disable interrupt for event DMARXMATCH[i]																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														
M	RW	DMATXEND			Enable or disable interrupt for event DMATXEND																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														
N	RW	DMATXREADY			Enable or disable interrupt for event DMATXREADY																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														
O	RW	DMATXBUSERROR			Enable or disable interrupt for event DMATXBUSERROR																														
					When this event is generated, the address which caused the error can be read from the BUSERRORADDRESS register.																														
			Disabled	0	Disable																														
			Enabled	1	Enable																														

8.23.10.23 INTENSET

Address offset: 0x304

Enable interrupt

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				O N M L K J I H G F																E D C				B				A							
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value	Description																														
A	RW	STOPPED W1S			Write '1' to enable interrupt for event STOPPED																														
			Set	1	Enable																														
			Disabled	0	Read: Disabled																														
			Enabled	1	Read: Enabled																														
B	RW	ERROR W1S			Write '1' to enable interrupt for event ERROR																														
			Set	1	Enable																														
			Disabled	0	Read: Disabled																														
			Enabled	1	Read: Enabled																														
C	RW	SUSPENDED W1S			Write '1' to enable interrupt for event SUSPENDED																														
			Set	1	Enable																														
			Disabled	0	Read: Disabled																														
			Enabled	1	Read: Enabled																														
D	RW	LASTRX W1S			Write '1' to enable interrupt for event LASTRX																														
			Set	1	Enable																														