

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value	Description																														
A	RW	EVENTS_TXDONE			TXSTATUS is changed to NoDataPending.																														
					MAILBOX.TXDATA has been read.																														
			NotGenerated	0	Event not generated																														
			Generated	1	Event generated																														

9.6.6.1.3 INTEN

Address offset: 0x300

Enable or disable interrupt

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0			
ID																																				B	A	
Reset 0x00000000				0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
ID	R/W	Field	Value ID	Value	Description																																	
A	RW	RXREADY			Enable or disable interrupt for event RXREADY																																	
					New data is available in MAILBOX.RXDATA.																																	
			Disabled	0	Disable																																	
			Enabled	1	Enable																																	
B	RW	TXDONE			Enable or disable interrupt for event TXDONE																																	
					MAILBOX.TXDATA has been read.																																	
			Disabled	0	Disable																																	
			Enabled	1	Enable																																	

9.6.6.1.4 INTENSET

Address offset: 0x304

Enable interrupt

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
ID																																				B	A
Reset 0x00000000				0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
ID	R/W	Field	Value ID	Value	Description																																
A	RW	RXREADY			Write '1' to enable interrupt for event RXREADY																																
					New data is available in MAILBOX.RXDATA.																																
			Set	1	Enable																																
			Disabled	0	Read: Disabled																																
			Enabled	1	Read: Enabled																																
B	RW	TXDONE			Write '1' to enable interrupt for event TXDONE																																
					MAILBOX.TXDATA has been read.																																
			Set	1	Enable																																
			Disabled	0	Read: Disabled																																
			Enabled	1	Read: Enabled																																

9.6.6.1.5 INTENCLR

Address offset: 0x308

Disable interrupt