### 8.16.7.31 PSEL.LED

Address offset: 0x51C

Pin select for LED signal

| Bit number | | | | | | | 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 |
|---|---|---|---|---|---|---|---|
| ID | | | | | | | C                                                                    B B B A A A A |
| **Reset 0xFFFFFFFF** | | | | | | | 1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1 1 1 1 1 1 1 1 1 1 |
| ID | R/W | Field | | Value ID | | Value | Description |
| A | RW | PIN | | | | [0..31] | Pin number |
| B | RW | PORT | | | | [0..7] | Port number |
| C | RW | CONNECT | | | | | Connection |
| | | | | Disconnected | | 1 | Disconnect |
| | | | | Connected | | 0 | Connect |

### 8.16.7.32 PSEL.A

Address offset: 0x520

Pin select for A signal

| Bit number | | | | | | | 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 |
|---|---|---|---|---|---|---|---|
| ID | | | | | | | C                                                                    B B B A A A A |
| **Reset 0xFFFFFFFF** | | | | | | | 1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1 1 1 1 1 1 1 1 1 1 |
| ID | R/W | Field | | Value ID | | Value | Description |
| A | RW | PIN | | | | [0..31] | Pin number |
| B | RW | PORT | | | | [0..7] | Port number |
| C | RW | CONNECT | | | | | Connection |
| | | | | Disconnected | | 1 | Disconnect |
| | | | | Connected | | 0 | Connect |

### 8.16.7.33 PSEL.B

Address offset: 0x524

Pin select for B signal

| Bit number | | | | | | | 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 |
|---|---|---|---|---|---|---|---|
| ID | | | | | | | C                                                                    B B B A A A A |
| **Reset 0xFFFFFFFF** | | | | | | | 1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1  1 1 1 1 1 1 1 1 1 1 |
| ID | R/W | Field | | Value ID | | Value | Description |
| A | RW | PIN | | | | [0..31] | Pin number |
| B | RW | PORT | | | | [0..7] | Port number |
| C | RW | CONNECT | | | | | Connection |
| | | | | Disconnected | | 1 | Disconnect |
| | | | | Connected | | 0 | Connect |

### 8.16.7.34 DBFEN

Address offset: 0x528

Enable input debounce filters

NORDIC
SEMICONDUCTOR