

Base address 0

Bit number	31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																													
ID	A A																													
Reset 0x00000000	0 0																													
ID	R/W	Field	Value ID	Value	Description																									
A	RW	BASE0			Base address 0																									

8.17.14.136 BASE1

Address offset: 0xE30

Base address 1

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				A A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value								Description																							
A	RW	BASE1										Base address 1																							

8.17.14.137 PREFIX0

Address offset: 0xE34

Prefixes bytes for logical addresses 0-3

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				D D D D D D D D C C C C C C C C B B B B B B B A A A A A A A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value				Description																											
A-D	RW	AP[i] (i=0..3)						Address prefix i																											

8.17.14.138 PREFIX1

Address offset: 0xE38

Prefixes bytes for logical addresses 4-7

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				D D D D D D D D C C C C C C C C B B B B B B B A A A A A A A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value				Description																											
A-D	RW	AP[i] (i=4..7)						Address prefix i																											

8.17.14.139 TXADDRESS

Address offset: 0xE3C

Transmit address select