8.19.8.32 PSEL.MISO

Address offset: 0x608

Pin select for SDI signal

Bit number					31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0		
ID					C		B B B A A A A
Reset 0xFFFFFFFF					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
ID	R/W	Field	Value ID		Value	Description	
A	RW	PIN			[0..31]	Pin number	
B	RW	PORT			[0..7]	Port number	
C	RW	CONNECT				Connection	
			Disconnected		1	Disconnect	
			Connected		0	Connect	

8.19.8.33 PSEL.DCX

Address offset: 0x60C

Pin select for DCX signal

Bit number					31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0		
ID					C		B B B A A A A
Reset 0xFFFFFFFF					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
ID	R/W	Field	Value ID		Value	Description	
A	RW	PIN			[0..31]	Pin number	
B	RW	PORT			[0..7]	Port number	
C	RW	CONNECT				Connection	
			Disconnected		1	Disconnect	
			Connected		0	Connect	

8.19.8.34 PSEL.CSN

Address offset: 0x610

Pin select for CSN

Bit number					31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0		
ID					C		B B B A A A A
Reset 0xFFFFFFFF					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
ID	R/W	Field	Value ID		Value	Description	
A	RW	PIN			[0..31]	Pin number	
B	RW	PORT			[0..7]	Port number	
C	RW	CONNECT				Connection	
			Disconnected		1	Disconnect	
			Connected		0	Connect	

8.19.8.35 DMA.RX.PTR

Address offset: 0x704

RAM buffer start address

NORDIC
SEMICONDUCTOR