

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value	Description																														
A	RW	CSNPOL[i] (i=0..0)			Polarity of CSN output																														
			LOW	0	Active low (idle state high)																														
			HIGH	1	Active high (idle state low)																														

8.19.8.29 ORC

Address offset: 0x5C0

Byte transmitted after TXD.MAXCNT bytes have been transmitted in the case when RXD.MAXCNT is greater than TXD.MAXCNT

Bit number				31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0																															
ID				A A A A A A A A																															
Reset 0x00000000				0 0																															
ID	R/W	Field	Value ID	Value				Description																											
A	RW	ORC						Byte transmitted after TXD.MAXCNT bytes have been transmitted in the case when RXD.MAXCNT is greater than TXD.MAXCNT.																											

8.19.8.30 PSEL.SCK

Address offset: 0x600

Pin select for SCK

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0																													
ID				C																								B												B	B	A	A	A	A	A																		
Reset 0xFFFFFFFF				1																																1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
ID	R/W	Field	Value ID	Value				Description																																																								
A	RW	PIN		[0..31]				Pin number																																																								
B	RW	PORT		[0..7]				Port number																																																								
C	RW	CONNECT						Connection																																																								
			Disconnected	1				Disconnect																																																								
			Connected	0				Connect																																																								

8.19.8.31 PSEL.MOSI

Address offset: 0x604

Pin select for SDO signal

Bit number				31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0																												
ID				C																								B				B	B	A	A	A	A	A																									
Reset 0xFFFFFFFF				1																																1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
ID	R/W	Field	Value ID	Value				Description																																																							
A	RW	PIN		[0..31]				Pin number																																																							
B	RW	PORT		[0..7]				Port number																																																							
C	RW	CONNECT						Connection																																																							
			Disconnected	1				Disconnect																																																							
			Connected	0				Connect																																																							