

Bit number	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
ID	C																								B	B	B	A	A	A	A	
Reset OxFFFFFFF	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
ID	R/W	Field	Value ID		Value		Description																									
A	RW	PIN			[0..31]		Pin number																									
B	RW	PORT			[0..7]		Port number																									
C	RW	CONNECT							Connection																							
			Disconnected		1		Disconnect																									
			Connected		0		Connect																									

8.25.13.34 PSEL.CTS

Address offset: 0x608

Pin select for CTS signal

Bit number	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
ID	C																							B	B	B	A	A	A	A	A	
Reset OxFFFFFFF	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
ID	R/W	Field	Value ID	Value		Description																										
A	RW	PIN		[0..31]		Pin number																										
B	RW	PORT		[0..7]		Port number																										
C	RW	CONNECT				Connection																										
			Disconnected	1		Disconnect																										
			Connected	0		Connect																										

8.25.13.35 PSEL.RXD

Address offset: 0x60C

Pin select for RXD signal

Bit number	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
ID	C																								B	B	B	A	A	A	A	
Reset OxFFFFFFF	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
ID	R/W	Field	Value ID	Value	Description																											
A	RW	PIN		[0..31]	Pin number																											
B	RW	PORT		[0..7]	Port number																											
C	RW	CONNECT			Connection																											
			Disconnected	1	Disconnect																											
			Connected	0	Connect																											

8.25.13.36 PSEL.RTS

Address offset: 0x610

Pin select for RTS signal