

8.14.2 Module operation. . . . .	399
8.14.3 Decimation filter. . . . .	400
8.14.4 EasyDMA. . . . .	400
8.14.5 Hardware example. . . . .	401
8.14.6 Pin configuration. . . . .	403
8.14.7 Registers. . . . .	403
8.15 PWM — Pulse width modulation. . . . .	414
8.15.1 Wave counter. . . . .	415
8.15.2 Decoder with EasyDMA. . . . .	418
8.15.3 Limitations. . . . .	426
8.15.4 Pin configuration. . . . .	426
8.15.5 Registers. . . . .	426
8.16 QDEC — Quadrature decoder. . . . .	447
8.16.1 Sampling and decoding. . . . .	447
8.16.2 LED output. . . . .	448
8.16.3 Debounce filters. . . . .	448
8.16.4 Accumulators. . . . .	449
8.16.5 Output/input pins. . . . .	449
8.16.6 Pin configuration. . . . .	450
8.16.7 Registers. . . . .	450
8.17 RADIO — 2.4 GHz radio. . . . .	465
8.17.1 Packet configuration. . . . .	465
8.17.2 Address configuration. . . . .	467
8.17.3 Data whitening. . . . .	467
8.17.4 CRC. . . . .	468
8.17.5 Radio states. . . . .	468
8.17.6 Transmit sequence. . . . .	470
8.17.7 Receive sequence. . . . .	471
8.17.8 Received signal strength indicator (RSSI). . . . .	473
8.17.9 Interframe spacing (IFS). . . . .	473
8.17.10 Device address match. . . . .	474
8.17.11 Bit counter. . . . .	475
8.17.12 IEEE 802.15.4 operation. . . . .	475
8.17.13 EasyDMA. . . . .	485
8.17.14 Registers. . . . .	486
8.18 SAADC — Successive approximation analog-to-digital converter. . . . .	554
8.18.1 Shared resources. . . . .	554
8.18.2 Overview. . . . .	555
8.18.3 Digital output. . . . .	555
8.18.4 Analog inputs and channels. . . . .	556
8.18.5 Operation modes. . . . .	556
8.18.6 EasyDMA. . . . .	559
8.18.7 Reference. . . . .	560
8.18.8 Acquisition time. . . . .	560
8.18.9 Limits event monitoring. . . . .	561
8.18.10 Performance factors. . . . .	562
8.18.11 Registers. . . . .	563
8.19 SPIM — Serial peripheral interface controller with EasyDMA. . . . .	582
8.19.1 SPIM transaction sequence. . . . .	583
8.19.2 D/CX functionality. . . . .	584
8.19.3 Chip select hardware control. . . . .	585
8.19.4 Pin configuration. . . . .	586
8.19.5 Shared resources. . . . .	587
8.19.6 EasyDMA. . . . .	587