

8.15.5.21.1.2 PUBLISH_DMASEQ[n].READY (n=0..1)

Address offset: 0x1A8 + (n × 0xC)

Publish configuration for event **READY**

Bit number		31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0			
ID	B	A A A A A A A A			
Reset 0x00000000		0 0			
ID	R/W	Field	Value ID	Value	Description
A	RW	CHIDX	[0..255]	DPPI channel that event READY will publish to	
B	RW	EN			
		Disabled	0	Disable publishing	
		Enabled	1	Enable publishing	

8.15.5.21.1.3 PUBLISH_DMASEQ[n].BUSERRORE (n=0..1)

Address offset: 0x1AC + (n × 0xC)

Publish configuration for event **BUSERRORE**

When this event is generated, the address which caused the error can be read from the **BUSERROREADDRESS** register.

Bit number		31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0			
ID	B	A A A A A A A A			
Reset 0x00000000		0 0			
ID	R/W	Field	Value ID	Value	Description
A	RW	CHIDX	[0..255]	DPPI channel that event BUSERRORE will publish to	
B	RW	EN			
		Disabled	0	Disable publishing	
		Enabled	1	Enable publishing	

8.15.5.22 PUBLISH_COMPAREMATCH[n] (n=0..3)

Address offset: 0x1BC + (n × 0x4)

Publish configuration for event **COMPAREMATCH[n]**

Bit number		31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0			
ID	B	A A A A A A A A			
Reset 0x00000000		0 0			
ID	R/W	Field	Value ID	Value	Description
A	RW	CHIDX	[0..255]	DPPI channel that event COMPAREMATCH[n] will publish to	
B	RW	EN			
		Disabled	0	Disable publishing	
		Enabled	1	Enable publishing	

8.15.5.23 SHORTS

Address offset: 0x200

Shortcuts between local events and tasks