

EXPERIMENT 6

**Student Name: Aman Raj Ojha
CSE (AIML)**

**UID: 24BAI70520 Branch: AIT-
Section/Group: 24AIT_KRG-G2 Semester: 4
Subject Name: Database Management System**

Subject Code: 24CSH-298

Experiment 6 – Understanding and Implementing Cursors for Row-by-Row Data Processing (Oracle, Accenture, Scaler, D. E. Shaw & Co)

Experiment

Experiment 6: Working with PL/SQL cursors to process multiple rows of a table individually. This experiment demonstrates the use of implicit cursors, explicit cursors, and cursor attributes to implement business logic on row-by-row data in Oracle and PostgreSQL.

Aim

To understand the concept and working of cursors in PL/SQL for row-by-row data processing, and to analyze how implicit cursors, explicit cursors, and cursor attributes are used to implement business logic on multiple rows in a database table.

Objective

- To implement and analyze implicit cursors for single-row operations.
- To implement explicit cursors to fetch and process multiple records.
- To apply cursor attributes (%FOUND, %NOTFOUND, %ROWCOUNT, %ISOPEN) for controlling program flow.
- To process employee records row by row and apply business logic effectively.

Software Requirements

Database Management System:

EXPERIMENT 6

- Oracle Database Express Edition (Oracle XE)
- PostgreSQL Database

Database Administration Tool / Client Tool:

- Oracle SQL Developer (for Oracle XE)
- pgAdmin (for PostgreSQL)

Problem Statement

In real-world enterprise applications, database queries often return multiple rows that need to be processed individually to apply specific business rules. Using cursors allows row-by-row processing for detailed business logic implementation.

Practical / Experiment Steps

1. Design PL/SQL programs that demonstrate:
 - The use of implicit cursors for single-row DML operations
 - The use of explicit cursors to fetch and process multiple records
 - The application of cursor attributes to control program execution
2. Create PL/SQL programs to:
 - Fetch employee records from a database table using cursors
 - Process each record individually
 - Display results or apply business logic using cursor attributes

Procedure

1. Open Oracle SQL Developer or pgAdmin and connect to the database.
2. Create an employee table with sample data (id, name, department, salary).
3. Write an anonymous PL/SQL block demonstrating implicit cursor operations.

EXPERIMENT 6

4. Write a PL/SQL block using an explicit cursor to fetch and process multiple records.
5. Apply cursor attributes such as %FOUND, %NOTFOUND, %ROWCOUNT, %ISOPEN to control execution flow.
6. Execute the blocks and observe the output.
7. Capture results and screenshots for documentation.

Input / Output Details Input

employee table:

- id (Integer)
- name (Varchar)
- department (Varchar)
- salary (Integer)

Cursor logic used:

- Implicit cursor for single-row processing
- Explicit cursor for multi-row processing
- Cursor attributes (%FOUND, %NOTFOUND, %ROWCOUNT, %ISOPEN)

Step-wise Output

Step 1 – Create employee Table

EXPERIMENT 6

[SQL Worksheet]*



```
1 CREATE TABLE EMPLOYEE (  
2     EMP_ID NUMBER PRIMARY KEY,  
3     EMP_NAME VARCHAR2(50),  
4     SALARY NUMBER  
5 );  
6 |
```

Query result **Script output** DBMS output Explain Plan SQL history



Table EMPLOYEE dropped.

Elapsed: 00:00:00.035

```
SQL> CREATE TABLE EMPLOYEE (  
      EMP_ID NUMBER PRIMARY KEY,  
      EMP_NAME VARCHAR2(50),  
      SALARY NUMBER...
```

[Show more...](#)

Table EMPLOYEE created.

Elapsed: 00:00:00.012

Step 2 – Insert Data into employee Table

EXPERIMENT 6

[SQL Worksheet]*



```
1 CREATE TABLE EMPLOYEE (  
2     EMP_ID NUMBER PRIMARY KEY,  
3     EMP_NAME VARCHAR2(50),  
4     SALARY NUMBER  
5 );  
6 INSERT INTO EMPLOYEE VALUES (101, 'Amit', 25000);  
7 INSERT INTO EMPLOYEE VALUES (102, 'Riya', 32000);  
8 INSERT INTO EMPLOYEE VALUES (103, 'Rahul', 45000);  
9 INSERT INTO EMPLOYEE VALUES (104, 'Sneha', 28000);  
10 INSERT INTO EMPLOYEE VALUES (105, 'Arjun', 50000);  
11  
12 COMMIT;
```

Query result **Script output** DBMS output Explain Plan SQL history



1 row inserted.

Elapsed: 00:00:00.002

SQL> COMMIT

Commit complete.

Elapsed: 00:00:00.002

Step 3 – Implicit Cursor Operation

EXPERIMENT 6

[SQL Worksheet]*

```

13
14 BEGIN
15     UPDATE EMPLOYEE
16     SET SALARY = SALARY * 1.10
17     WHERE SALARY < 30000;
18
19     DBMS_OUTPUT.PUT_LINE('Rows Updated: ' || SQL%ROWCOUNT);
20
21     IF SQL%FOUND THEN
22         DBMS_OUTPUT.PUT_LINE('Update Successful');
23     END IF;
24 END;
25 /

```

Query result
Script output
DBMS output
Explain Plan
SQL history

SQL> BEGIN
UPDATE EMPLOYEE
SET SALARY = SALARY * 1.10
WHERE SALARY < 30000;...
Show more...

Rows Updated: 2
Update Successful

PL/SQL procedure successfully completed.
Elapsed: 00:00:00.091

Terms and Conditions
Your Privacy Rights
Delete Your FreeSQL Account
Cookie Preferences
26.12 - Copyright © 20

Step 4 – Explicit Cursor Declaration and Fetch

EXPERIMENT 6

```

26
27 DECLARE
28     CURSOR emp_cursor IS
29         SELECT EMP_ID, EMP_NAME, SALARY FROM EMPLOYEE
30         WHERE SALARY > 30000;
31
32     v_id EMPLOYEE.EMP_ID%TYPE;
33     v_name EMPLOYEE.EMP_NAME%TYPE;
34     v_salary EMPLOYEE.SALARY%TYPE;
35
36 BEGIN
37     OPEN emp_cursor;
38
39     LOOP
40         FETCH emp_cursor INTO v_id, v_name, v_salary;
41         EXIT WHEN emp_cursor%NOTFOUND;
42

```

Query result **Script output** DBMS output Explain Plan SQL history



```

SQL> DECLARE
      CURSOR emp_cursor IS
          SELECT EMP_ID, EMP_NAME, SALARY FROM EMPLOYEE
          WHERE SALARY > 30000;...

```

[Show more...](#)

```

ID: 102 Name: Riya Salary: 32000
ID: 103 Name: Rahul Salary: 45000
ID: 104 Name: Sneha Salary: 30800
ID: 105 Name: Arjun Salary: 50000

```

PL/SQL procedure successfully completed.

Elapsed: 00:00:00.079

EXPERIMENT 6

[SQL Worksheet]*      Aa   

```
54 DECLARE
55     CURSOR emp_cursor IS SELECT * FROM EMPLOYEE;
56     emp_record EMPLOYEE%ROWTYPE;
57
58 BEGIN
59     OPEN emp_cursor;
60
61     IF emp_cursor%ISOPEN THEN
62         DBMS_OUTPUT.PUT_LINE('Cursor Opened Successfully');
63     END IF;
64
65     LOOP
66         FETCH emp_cursor INTO emp_record;
67         EXIT WHEN emp_cursor%NOTFOUND;
68
69         DBMS_OUTPUT.PUT_LINE(
70             'Employee: ' || emp_record.EMP_NAME ||
```

Query result **Script output** DBMS output Explain Plan SQL history

 

...
Show more...

Cursor Opened Successfully
Employee: Amit | Salary: 27500
Employee: Riya | Salary: 32000
Employee: Rahul | Salary: 45000
Employee: Sneha | Salary: 30800
Employee: Arjun | Salary: 50000
Total Rows Processed: 5

PL/SQL procedure successfully completed.

Elapsed: 00:00:00.020

[Terms and Conditions](#) [Your Privacy Rights](#) [Delete Your FreeSQL Account](#) [Cookie Preferences](#) 26.1.2 - Copyright © 2020

Learning Outcome

After completing this experiment, the learner will be able to:

- Understand the role of cursors in PL/SQL for handling multi-row query results.
- Differentiate between implicit cursors and explicit cursors.

EXPERIMENT 6

- Use cursor attributes such as %FOUND, %NOTFOUND, %ROWCOUNT, and %ISOPEN.
- Develop PL/SQL programs that process database records row by row.
- Apply cursor-based logic in real-world business scenarios used in organizations like Oracle, Accenture, Scaler, and D. E. Shaw & Co.