

# Dimensionality Reduction

Steve Avsec

Illinois Institute of Technology

April 22, 2024

# Overview

1 Locality-Sensitive Hashing

2 Differential Privacy

# Distances

A "distance" function has to have the following properties:

- $d(x, y) \geq 0$ .

# Distances

A "distance" function has to have the following properties:

- $d(x, y) \geq 0$ .
- $d(x, y) = 0 \Leftrightarrow x = y$ .

# Distances

A "distance" function has to have the following properties:

- $d(x, y) \geq 0$ .
- $d(x, y) = 0 \Leftrightarrow x = y$ .
- $d(x, y) = d(y, x)$ .

# Distances

A "distance" function has to have the following properties:

- $d(x, y) \geq 0$ .
- $d(x, y) = 0 \Leftrightarrow x = y$ .
- $d(x, y) = d(y, x)$ .
- $d(x, z) \leq d(x, y) + d(y, z)$ .

# Some Examples

- Jaccard distance on sets:

$$d(A, B) = 1 - \frac{|A \cap B|}{|A \cup B|}$$

# Some Examples

- Jaccard distance on sets:

$$d(A, B) = 1 - \frac{|A \cap B|}{|A \cup B|}$$

- Hamming distance on vectors:

$$d(\mathbf{x}, \mathbf{y}) = |\{j : x_j \neq y_j\}|$$



# Some Examples

- Jaccard distance on sets:

$$d(A, B) = 1 - \frac{|A \cap B|}{|A \cup B|}$$

- Hamming distance on vectors:

$$d(\mathbf{x}, \mathbf{y}) = |\{j : x_j \neq y_j\}|$$

- Euclidean distance:

$$d(\mathbf{x}, \mathbf{y}) = \sum_{j=1}^N |x_j - y_j|^2$$

# Some Examples

- Jaccard distance on sets:

$$d(A, B) = 1 - \frac{|A \cap B|}{|A \cup B|}$$

- Hamming distance on vectors:

$$d(\mathbf{x}, \mathbf{y}) = |\{j : x_j \neq y_j\}|$$

- Euclidean distance:

$$d(\mathbf{x}, \mathbf{y}) = \sum_{j=1}^N |x_j - y_j|^2$$

- Edit distance on strings (also equal to the longest common subsequence).

# Locality-Sensitive Functions

A family of functions  $\mathbf{F}$  is said to be  $(d_1, d_2, p_1, p_2)$ -sensitive with respect to some distance if for every function  $f \in \mathbf{F}$

- $d(x, y) \leq d_1$  implies that  $f(x) = f(y)$  with probability at least  $p_1$ .
- $d(x, y) \geq d_2$  implies that  $f(x) = f(y)$  with probability at most  $p_2$ .

# Locality-Sensitive Functions

A family of functions  $\mathbf{F}$  is said to be  $(d_1, d_2, p_1, p_2)$ -sensitive with respect to some distance if for every function  $f \in \mathbf{F}$

- $d(x, y) \leq d_1$  implies that  $f(x) = f(y)$  with probability at least  $p_1$ .
- $d(x, y) \geq d_2$  implies that  $f(x) = f(y)$  with probability at most  $p_2$ .

Example: Minhash and Jaccard distance is  $(d_1, d_2, 1 - d_1, 1 - d_2)$ -sensitive for  $0 \leq d_1 < d_2 \leq 1$ .

# Locality-Sensitive Functions

A family of functions  $\mathbf{F}$  is said to be  $(d_1, d_2, p_1, p_2)$ -sensitive with respect to some distance if for every function  $f \in \mathbf{F}$

- $d(x, y) \leq d_1$  implies that  $f(x) = f(y)$  with probability at least  $p_1$ .
- $d(x, y) \geq d_2$  implies that  $f(x) = f(y)$  with probability at most  $p_2$ .

Example: Minhash and Jaccard distance is  $(d_1, d_2, 1 - d_1, 1 - d_2)$ -sensitive for  $0 \leq d_1 < d_2 \leq 1$ .

For Hamming distance, the coordinate functions  $f_i(\mathbf{x}) = x_i$  are  $(d_1, d_2, 1 - \frac{d_1}{N}, 1 - \frac{d_2}{N})$ -sensitive since the probability of agreement for a single  $f_i$  is exactly  $1 - \frac{d(x,y)}{N}$ .

# Definition

A randomized algorithm  $\mathcal{A}$  which takes a database as input is said to provide  $(\epsilon, \delta)$ -differential privacy if for datasets  $D_1$  and  $D_2$  that differ on a single element and all subsets  $S \subseteq \text{range}(\mathcal{A})$ :

$$P(\mathcal{A}(D_1) \in S) \leq e^\epsilon P(\mathcal{A}(D_2) \in S) + \delta$$

# Big Idea

Using distances like the Hamming distance and other distances that are similar plus some ideas from locality-sensitive hashing, one can create queries that compute

- Sums
- Counts
- Averages
- Mins and maxes

that provide differential privacy.