

Low Cost Porta Cabin — Technical Specifications & Price List

Entry-level specification — the value line of the SAMAN porta cabin range, for tenders and client approvals.

Every SAMAN low cost porta cabin is factory-fabricated at our Bengaluru and Greater Noida units on the same welded 100×50×3 mm MS C-channel chassis as our standard line — cost reduction comes from lighter wall/roof sheet gauge and economical internal finishes, never by removing or reducing the welded steel frame. The shell is 0.8–1.0 mm corrugated MS sheet with a 1.2 mm corrugated sloped roof; interiors are finished in 6 mm pre-laminated board, insulated with 12 mm heatlon or 25 mm glass wool in the walls and 25–50 mm glass wool below the roof, over an 18 mm BWP plywood floor with 1.5 mm vinyl finish. One specification, nine standard sizes — only quantities, fit-out, transport and price change with size. Anything not listed below is confirmed at quotation.

Frame Retained at Every Tier	GST Registered	5-Year Structural Warranty	Pan-India Delivery
------------------------------	----------------	----------------------------	--------------------

Sizes & Prices — base specification, ex-GST

SIZE	DIMENSIONS	AREA (SQ FT)	COMFORTABLY FITS	PRICE (RS, EX-GST)
10×10 ft	10×10×8.5 ft	100	2–3 people	1,32,000
20×8 ft	20×8×8.5 ft	160	3–4 people	2,11,200
20×10 ft	20×10×8.5 ft	200	4–6 people	2,40,000
20×12 ft	20×12×8.5 ft	240	5–7 people	2,76,480
30×10 ft	30×10×8.5 ft	300	6–8 people	3,45,600
40×8 ft	40×8×8.5 ft	320	7–9 people	3,60,960
20×20 ft	20×20×8.5 ft	400	8–10 people	4,51,200
40×10 ft	40×10×8.5 ft	400	8–10 people	4,51,200
40×12 ft	40×12×8.5 ft	480	10–12 people	5,29,920

Prices are complete-cabin, base-specification prices — roughly Rs 1,104–1,320 per sq ft ex-GST across the nine sizes, about 4% below our standard porta cabin line. GST 18% extra · HSN 9406 (prefabricated buildings). Customisations, interior fit-out, transport and installation are quoted separately. Delivery across South & North India, typically 7–21 working days. Free delivery: Bengaluru city (South) and Delhi NCR — Ghaziabad, Gurugram, Faridabad, Noida, Greater Noida (North).

Warranty: 5-year structural warranty · 1–2 years on finishing and fitments · bought-out electrical, sanitary and hardware items carry their manufacturers' warranty. Full terms confirmed at quotation.

Steel Structure

COMPONENT	SPECIFICATION	DETAIL
Bottom frame	100×50×3 mm MS C-channel	Primary load-bearing chassis — identical to the standard line (20×10 reference).
Bottom stiffeners	75×40×2 mm channels and 50×50×2 mm MS square pipes at ~4 ft centres	Reinforces the floor and distributes occupancy and equipment loads.
Floor frame	50×50×2 mm MS square-pipe floor supports	Supports the floor board and finished floor.
Top frame	50×50×1.6 mm MS square-pipe top perimeter	Main upper perimeter and wall-head support.

COMPONENT	SPECIFICATION	DETAIL
Roof stiffeners	40×20×1.6 mm and 40×40×1.6 mm MS roof members	Roof slope, stiffness, ceiling support and service openings.
Corner posts / walls	40×40×2 mm MS square-pipe corner and intermediate posts	Frames corners, wall panels, doors, windows and partitions.
Lifting hooks	As per approved cabin weight and lifting design	Welded lifting points for crane handling, loading and relocation.
Welding & fabrication	As per approved fabrication drawing	Structural joints welded, cleaned and protected before linings close.

Walls, Roof, Floor & Insulation

COMPONENT	SPECIFICATION	DETAIL
Exterior walls	0.8–1.0 mm corrugated MS sheet	Mandatory factory-fabricated external shell (lighter gauge — the economy lever).
Roof	1.2 mm corrugated MS sheet	Sloped, sealed and flashed for water drainage.
Interior walls	6 mm pre-laminated plywood/board	Economical finished internal lining.
Ceiling	6 mm pre-laminated ceiling board	Supports lighting; completes the internal finish.
Floor base	18 mm BWP plywood	Fixed over the welded MS floor frame.
Floor finish	1.5 mm vinyl flooring	Selected for traffic, moisture and hygiene.
Wall insulation	12 mm heatlon or 25 mm glass wool	Installed within the wall cavity.
Roof insulation	25–50 mm glass wool	Installed below the corrugated MS roof sheet.
External finish	Anti-rust enamel in an approved colour combination	Optional façade cladding fitted above the corrugated shell where specified.
Fasteners & sealing	Self-tapping fasteners, welding, sealant, gaskets and flashing	Weather sealing at roof, corners, doors, windows and penetrations.

Doors, Windows, Electrical & Services

COMPONENT	SPECIFICATION	DETAIL
Main door	32 mm waterproof flush door with MS frame and standard hardware	Opens outward; quantity and position per approved layout.
Windows	Powder-coated aluminium sliding windows, 3 mm glass	Quantity, size and position per approved layout.
Grills / mesh	MS safety grill and mosquito mesh, per site requirements	Selected for security, visibility and ventilation.
Electrical wiring	PVC-insulated copper: 1.5 sq mm lighting · 2.5 sq mm sockets · 4 sq mm AC/high-load	Concealed wiring for 240 V, 50 Hz single-phase supply.
Electrical protection	Mini DB with MCB protection, rated per final load schedule	Separate protection for lighting, socket, AC and equipment circuits.
Electrical fittings	LED lights, modular switches, 6A/16A sockets, fan points, AC provision	Point quantity and rating per the approved layout.

COMPONENT	SPECIFICATION	DETAIL
Ventilation / AC	Natural cross ventilation; fan, exhaust and AC provision as required	Final equipment based on occupancy and use.
Plumbing / sanitary	CPVC / UPVC sanitary and kitchen services	Included only where listed in the approved scope.
Layout	Open single-room layout	Furniture and partitions finalised by approved drawing.
Painting	Red-oxide/epoxy primer + anti-rust enamel — 1 primer + 2 enamel coats	Applied after cleaning; touch-up after handling and dispatch.
Quality checks	Pre-dispatch inspection, checklist basis	Dimensions, welding, paint, leakage, openings, electricals and finish.

Where the saving comes from — and where it never does. Cost reduction on this line is achieved through lower wall/roof sheet gauge and economical internal finishes, not by removing or lightening the welded steel frame. The same specification applies to all nine standard sizes; materials, thicknesses and the door/window package do not change when you change size. Any engineering strengthening required for a confirmed order is issued as a separately approved technical deviation. Need PUF-panel insulation or a higher interior grade? The same cabin steps up to our standard and luxury porta cabin lines.

Get a fixed-price quote in 48 hours

South — Bengaluru

+91 88616 22859

sales@samanportable.com

North — Greater Noida (Delhi NCR)

+91 87960 39938

ncr@samanportable.com

Pan-India enquiries: +91 97089 89937 · www.samanportable.com